

CONSTRUCTION

Overall Grade/Function: Premium Grade
Backing: Waterproof, lusterless, vinyl film with a carrier of cotton cloth
Adhesive: Natural rubber

PHYSICAL CHARACTERISTICS

STANDARD

METRIC

	STANDARD		METRIC	
Tensile Strength	46	lbs./in. width	80.6	N/10mm
Adhesion to Stainless Steel	50	oz./in. width	5.47	N/10mm
Thickness	12.0	mils	.30	mm
Elongation	5	%	5	%
Maximum Temperature	50° to 200°	F	10° to 93°	C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

COLOR (S)

Black (BLK) Burgundy (BUR) Olive Drab (OLV) Yellow (YEL)
 Blue (BLU) Gray (GRY) Red (RED)
 Brown (BRN) Green (GRN) White (WHI)

APPLICATIONS

- Gaffer's tape in A/V, TV, photography, theatrical and motion picture industries to hold wiring, lighting, stage props and to color code
- Masking silk screen frames
- Waterproof packaging
- Other uses requiring the physical characteristics and benefits of this lusterless tape

PRODUCT BENEFITS

- Waterproof backing
- Indoor/outdoor use
- Very high holding power
- Excellent conformability
- Excellent adhesion
- Minimum residue
- Durable and strong
- Excellent outdoor weathering features
- Very high tensile strength

APPLICABLE SPECIFICATIONS

A-A-1586

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

ISO 9000 CERTIFIED QUALITY SYSTEM

Shurtape Technologies, LLC

1506 Highland Avenue NE, Hickory, NC 28601 • PO Box 1530, Hickory, NC 28603-1530
 Phone 828/322-2700 or 888/442-TAPE • Fax 828/322-4419 • Customer Service Fax 828/322-4029 or
 800/335-7651